

GALP FORMULA LS LONGLIFE III 5W30

Fully synthetic, top performance lubricant, specially developed to meet the specifications for Volkswagen group engines: **VW 504.00** (gasoline) and **VW 507.00** (Diesel) used in specific car models.

It provides "Super Fuel Economy" rates and is ideal for long oil-change intervals for all vehicles.

This product improves fleet performance and can be used in all applications that demand VW500.00, VW501.00, VW501.01, VW502.00, VW503.00, VW503.01, VW505.00, VW505.01, VW506.00 e VW506.01 (except R5 TDI (2,5 L) e V10 TDI (5,0L) models).

PROPERTIES

- Its high fluidity at low temperatures ensures adequate engine lubrication during starting.
- Excellent anti-wear protection.
- Excellent lubricating film stability which maintains all its properties, even under extreme pressure and temperature conditions.
- More available power whilst reducing fuel and lubricant consumption.
- High thermal stability and resistance against oxidation, preventing the build-up of sludge, varnishes and other deposits.
- Helps catalyst converters function more efficiently and last longer and reduces emissions levels, thus making a positive contribution to environmental protection.

SPECIFICATIONS/APPROVALS

- **ACEA C3**
- **VW 504.00 / 507.00**
- **PORSCHE C30**
- **API SN**
- **MB-APPROVAL 229.51**
- **BMW LL-04**

MAIN CHARACTERISTICS

TESTS	METHODS	RESULTS
SAE Grade	---	5W-30
Density at 15°C, kg / l	ASTM D1298/ D4052	0,85
Viscosity index	ASTM D2270	174
Kinematic viscosity at 100°C, mm ² /s	ASTM D445/ D7042	10,8
Pour point, °C	ASTM D97/ D6892	- 42
Flash point, °C	ASTM D92	231

PACKAGING



The values shown are for guidance and do not constitute a specification. This information may include minor variations that do not affect the product's performance. The information in this file is of a general nature and no guarantee is given if the products are used incorrectly or the information is out of date. To get a copy of the Safety Data Sheet for this product, please contact GALP's Customer Services Centre: export@galp.com.

GALP | R. Tomás da Fonseca, Torre C, 1600-209, Lisboa, Portugal
galp.com