

GALP TRANSMATIC DII

DEXRON II type lubricant for automatic gearboxes, power steering and hydraulic systems.

PROPERTIES

- Excellent anti-wear properties.
- Good balance between static and dynamic friction coefficients.
- High antioxidant power, ensuring that the lubricant film maintains its characteristics unchanged over an extended period, even when subjected to extreme conditions of temperature and pressure.
- High stability and compatibility with the equipment, helping in protecting the critical components of the hydraulic pump and preventing oil leakage.
- High seal compatibility.

MAIN CHARACTERISTICS

TESTS	METHODS	RESULTS
Colour	Visual	Red
Density at 15°C, kg / l	ASTM D1298/ D4052	0,87
Viscosity index	ASTM D2270	175
Kinematic viscosity at 40°C, mm²/s	ASTM D445/ D7042	38,5
Kinematic viscosity at 100°C, mm²/s	ASTM D445/ D7042	7,7
Pour point, °C	ASTM D97/ D6892	-48
Flash point, °C	ASTM D92	226
FZG Test (A/8.3/90):	DIN 51354	
– Pass load stage		11

SPECIFICATIONS/APPROVALS

- **GM** DEXRON II-D
- **MAN** 339 Type Z-1, V-1, L-2
- **MB** 236.1; 236.7
- **FORD** MERCON
- **FORD** M2C 138-CJ; M2C 166-H
- **VOITH** (DIWA e Midimat) 55.6335.36 (G607)
- **VOLVO** 97335; 97325
- **CATERPILLAR** TO-2
- **ZF** TE-ML 03D, 05L, 09, 11A, 17C
- **ZF** TE-ML 04D, 14A (ZF ZF000331)
- **DENISON** HF-0
- **VICKERS** M-2950-S; I-286-S
- **SUNDSTRAND-SAUER**
- **ALLISON** C-4

PACKAGING



The values shown are for guidance and do not constitute a specification. This information may include minor variations that do not affect the product's performance. The information in this file is of a general nature and no guarantee is given if the products are used incorrectly or the information is out of date. To get a copy of the Safety Data Sheet for this product, please contact GALP's Customer Services Centre: export@galp.com.

GALP | R. Tomás da Fonseca, Torre C, 1600-209, Lisboa, Portugal
galp.com