

GALP TRANSOIL XT 75W80

Fully synthetic lubricant incorporating the most advanced additive technology, specially developed for lubricating manual gearboxes. Because it is completely synthetic, it has exceptional characteristics of thermal stability and cleanliness, suitable for conditions of severe use and subject to high temperatures.

PROPERTIES

- Excellent thermal stability.
- Optimum resistance to high loads.
- Compatible with most elastomers.
- Excellent rust resistance performance.
- Good fluidity at low temperature.

SPECIFICATIONS/APPROVALS

API GL-4 VW / AUDI

- TL 726 (80W)
- VW 501 50 (G 005 000 05 / G 005 000 / G 005 000 20 / G 052 911 A1/A2), G 055 538 A2G 009 317, G 50
- Audi TL 52532, G 052 171, G 052 178, G 052 512, G052 532, G 052 527, G 052 726

RENAULT - NISSAN

- Nissan 999MP-MTF20P
- KE91699932R
- Nissan MT-XZ

PSA

- PSA B71 2330
- PSA B71 2315
- PSA 9730A2
- PSA 9730A8

FORD

- WSS-M2C200-C/C2/C3
- WSS-M2C200-D2, 1547953, 1382914
- ESD-M2C186-A
- WSD-M2C200-D

The values shown are for guidance and do not constitute a specification. This information may include minor variations that do not affect the product's performance. The information in this file is of a general nature and no guarantee is given if the products are used incorrectly or the information is out of date. To get a copy of the Safety Data Sheet for this product, please contact GALP's Customer Services Centre: export@galp.com.

OPEL

- Opel 19 40 182
- Opel 19 40 757
- Opel 19 40 768
- Opel 19 40 776

GM

- GM 1940711
- GM 1940776
- GM 88861800
- GM 88861801
- GM 1940182
- GM 1940757
- GM 1940768

FIAT (FCA)

- Fiat 9.55550, CTR F178.B06
- Fiat CTR F921.B10 14621616
- Fiat 9.55550-MX3
- Fiat 9.55550-MZ1

BMW

- BMW 83 22 0 309 031
- BMW 83 22 0 403 247
- BMW 83 22 7 533 818
- BMW 2300 1434 404
- BMW 2300 7533 513
- BMW 2300 7533 818
- MTF LT1, LT2, LT3, LT4, LT5
- MB 235.10

MERCEDES-BENZ

TOYOTA

- Toyota 08885-00705
- Toyota JWS 227
- Hyundai 02200-00130 TOD

HYUNDAI

HONDA

- Honda 08261-99964
- Honda 08798-9031 MTF-7289 MTF 94
- Special Honda MTF
- Special Honda MTF-II

The values shown are for guidance and do not constitute a specification. This information may include minor variations that do not affect the product's performance. The information in this file is of a general nature and no guarantee is given if the products are used incorrectly or the information is out of date. To get a copy of the Safety Data Sheet for this product, please contact GALP's Customer Services Centre: export@galp.com.

VOLVO

- Volvo 97308
- Volvo 97309
- Volvo 97310
- Volvo 1161681
- Volvo 1161745

OTHERS

- Alfa Romeo
- Lancia
- Land Rover STC 9157
- Land Rover STC 9158
- Land Rover TYK500030
- Mitsubishi MZ312644 3005401 MTF-94
- MG and Mini Cooper
- Subaru K0321-F0090
- Amarok 0C6
- AC Delco 10-4033

MAIN CHARACTERISTICS

TESTS	METHODS	RESULTS
SAE Grade	SAE J306	75W-80
Density at 15°C, kg / l	ASTM D1298/ D4052	0,864
Viscosity index	ASTM D2270	183
Kinematic viscosity at 40°C, mm ² /s	ASTM D445/ D7042	42,6
Kinematic viscosity at 100°C, mm ² /s	ASTM D445/ D7042	8,6
Pour point, °C	ASTM D97-17b	-48
Flash Point, °C	ASTM D92	223

PACKAGING



DRUM 205L



PAIL 20L

The values shown are for guidance and do not constitute a specification. This information may include minor variations that do not affect the product's performance. The information in this file is of a general nature and no guarantee is given if the products are used incorrectly or the information is out of date. To get a copy of the Safety Data Sheet for this product, please contact GALP's Customer Services Centre: export@galp.com.

GALP | R. Tomás da Fonseca, Torre C, 1600-209, Lisboa, Portugal
galp.com